



## BEV-SEAL ULTRA® 175 SERIES

reinforced dual barrier hose

### REINFORCED BEV-SEAL ULTRA® HOSE

#### RECOMMENDED USE

All beverage applications where excellent barrier properties in combination with a strong yarn-reinforced hose is required.

#### KEY FEATURES AND CHARACTERISTICS

- Dual-Barrier construction, Glass-Flex™ inner liner and a seamless extruded barrier layer in a polyolefin core tube, reinforced with polyester yarn and protected by a smooth EVA cover;
- The flushable Glass-Flex™ liner, allows changeovers from even the most pungent flavours with simple flushing procedures;
- NSF certified under standard NSF-51 for food equipment and NSF-61 for drinking water systems;
- Polyester reinforcement;
- Phthalate free.



#### AVAILABLE PRODUCTS

- 175-04500-00 BeV-Seal Ultra 175 PE BTYB .265" x .420" White NT DB 500'152,4mS CS11.3mm
- 175-06300-00 BeV-Seal Ultra 175 PE BTYB .380" x .535" White NT DB 300'91,4mS CS14.5mm

#### PRODUCTS SPECIFICATIONS

Article number	Nominal ID inch	Nominal OD inch	Nominal ID mm	Nominal OD mm	Working Pressure at 21°C bar	Working Pressure at 60°C bar	Weight per Package kgs	Min. Bend Radius mm	Clamp Size mm	Standard Package ft	Standard Package m	Package type
175-04500-00	0.265	0.420	6.7	10.7	20.7	10.3	4.1	44.5	11.3	500	152.4	Boxed spool
175-06300-00	0.375	0.535	9.5	13.6	20.7	10.3	3.5	76.2	14.5	300	91.4	Boxed spool