

## BEV-SEAL ULTRA® 235 SERIES

ultimate flavour protection

### THE BEST TUBE THERE IS!

#### RECOMMENDED USE

Our best beverage transfer tube can be used for all beverage applications.

#### KEY FEATURES AND CHARACTERISTICS

- Flushable Glass-Flex™ inner liner surrounded by a seamless extruded barrier layer in a coextruded polyolefin tube;
- A second barrier prevents migration of gasses;
- Allows change-overs from even the most pungent flavours with simple flushing procedures;
- Certified under standard NSF-51 for food equipment and NSF-61 for drinking water systems.
- Check our python animation in which our Bev-Seal Ultra tube is explained too;
- Colour coded and numbered.



#### AVAILABLE PRODUCTS

235-0562X1K	Bev-Seal Ultra 235 PE BT NB .190" x .313" White NT DB 1000'304,8mSB CS8,7mm
235-06620-XX	Bev-Seal Ultra 235 PE BT NB .265" x .375" White NT DB 500'152,4mSB CS10,0mm
235-08620-XX	Bev-Seal Ultra 235 PE BT NB .380" x .500" White NT DB 500'152,4mSB CS14,0mm
23511.559000	Bev-Seal Ultra 235 PE BT NB 8.5 x 11.5mm White NT DB 150mSB CS12,3mm
235-10620x500	Bev-Seal Ultra 235 PE BT NB .510" x .625" White NT DB 500'152,4mCW CS17,0mm

#### PRODUCTS SPECIFICATIONS

Article number	Nominal ID inch	Nominal OD inch	Nominal ID mm	Nominal OD mm	Working Pressure at 21°C bar	Working Pressure at 60°C bar	Weight per Package kgs	Min. Bend Radius mm	Clamp Size mm	Standard Package ft	Standard Package m	Package type
235-0562X1K	0.190	0.313	4,8	7,9	10	3,5	10,8	25	8,7	1000	304,8	Boxed Spool
235-06620-XX	0.265	0.375	6,7	9,5	10	3,1	6	32	10	500	152,4	Boxed Coil
235-08620-XX	0.380	0.500	9,5	12,7	6,9	2,8	8,6	57	14	500	152,4	Boxed Coil
23.511.559.000	0.335	0.453	8,5	11,5	6,9	2,8		57	12,3	500	152,4	Boxed Coil
235-10620x500	0.510	0.625	12,9	15,9	5,2	2,1	9,4	254	17	500	152,4	Wrapped Coil