



PRODUCTS

BEVLEX® 170 SERIES

polyester-reinforced polyethylene beverage hose

REINFORCED POLYETHYLENE HOSE

RECOMMENDED USE

Our entry level hose for many different drink applications.



PRODUCT FEATURES AND CHARACTERISTICS

- Outperforming in pressure performance and kink-resistance;
- NSF-51/61 certified Food-Grade Materials;
- LLDPE core tube construction providing excellent resistance to stress cracking;
- Bonded abrasion-resistant co-polymer jacket, no separation in tight bends;
- Available with a white, red or blue tracer;
- Polyester reinforcement;
- Phthalate Free.

AVAILABLE PRODUCTS

| | |
|--------------|--|
| 170-04102-77 | Bevlex 170 PE BH YB .265" x .457" White NT 100'30,5mCB CS13,3mm |
| 170-04502-00 | Bevlex 170 PE BH YB .265" x .457" White NT 500'152,4mSB CS13,3mm |
| 170-04512-00 | Bevlex 170 PE BH YB .265" x .457" White RT 500'152,4mS CS13,3mm |
| 170-04522-00 | Bevlex 170 PE BH YB .265" x .457" White BT 500'152,4mS CS13,3mm |
| 170-06100-77 | Bevlex 170 PE BH YB .380" x .593" White NT 100'30,5mCB CS15,7mm |
| 170-06300-00 | Bevlex 170 PE BH YB .380" x .593" White NT 300'91,4mSB CS15,7mm |
| 170-06301-00 | Bevlex 170 PE BH YB .380" x .635" White NT 300'91,4mSB CS17,0mm |
| 170-08300-00 | Bevlex 170 PE BH YB .510" x .740" White NT 300'91,4mC CS19,8mm |

PRODUCTS SPECIFICATIONS

| Article number | Nominal ID inch | Nominal OD inch | Nominal ID mm | Nominal OD mm | Working Pressure at 21°C | Working Pressure at 50°C | Weight per Package | Min. Bend Radius | Clamp Size | Standard Package | Standard Package | Package type |
|----------------|-----------------|-----------------|---------------|---------------|--------------------------|--------------------------|--------------------|------------------|------------|------------------|------------------|--------------|
| | inch | inch | mm | mm | bar | Bar | kgs | mm | mm | ft | m | |
| 170-04102-77 | 0.265 | 0.457 | 6,7 | 11,6 | 20.7 | 10.3 | 2.8 | 27.9 | 13.3 | 100 | 30.5 | Boxed coil |
| 170-04502-00 | 0.265 | 0.457 | 6,7 | 11,6 | 20.7 | 10.3 | 11.4 | 27.9 | 13.3 | 500 | 152.4 | Boxed spool |
| 170-04512-00 | 0.265 | 0.457 | 6,7 | 11,6 | 20.7 | 10.3 | 11.4 | 27.9 | 13.3 | 500 | 152.4 | Boxed spool |
| 170-04522-00 | 0.265 | 0.457 | 6,7 | 11,6 | 20.7 | 10.3 | 11.4 | 27.9 | 13.3 | 500 | 152.4 | Boxed spool |
| 170-06100-77 | 0.380 | 0.593 | 9.7 | 15.1 | 20.7 | 10.3 | | 44.5 | | 100 | 30.5 | Boxed coil |
| 170-06300-00 | 0.380 | 0.593 | 9.7 | 15.1 | 20.7 | 10.3 | 10.4 | 44.5 | 15.7 | 300 | 91.4 | Boxed Spool |
| 170-06301-00 | 0.380 | 0.635 | 9.7 | 16.1 | 20.7 | 10.3 | 20.5 | 44.5 | 17.0 | 300 | 91.4 | Boxed Spool |
| 170-08300-00 | 0.510 | 0.740 | 12.9 | 18.8 | 17.2 | 8.6 | 12.2 | 76.2 | 19.8 | 300 | 91.4 | Boxed Spool |